

CROSS SECTION IN GRASSED AREAS

## (AS PER IRISH WATER. SEE STD-W-13)

- 1. ALL DIMENSIONS ARE IN MILIMETRES UNLESS NOTED OTHERWISE
- 2. THE MINIMUM DEPTH OF COVER FROM THE FINISHED GROUND LEVEL TO THE EXTERNAL CROWN OF THE PIPE SHALL BE 750mm FOR SERVICE CONNECTIONS. 900mm FOR WATER MAINS, GREATER DEPTHS OF COVER AND/OR PIPE STRENGTH AND/OR A HIGHER CLASS OF BEDDING MATERIAL MAY BE REQUIRED WHERE HIGH TRAFFIC LOADING IS ANTICIPATED. THE MAXIMUM COVER SHOULD NOT EXCEED 1.2m WHERE PRACTICABLE.
- 3. CLAUSE 808 MATERIAL IN ACCORDANCE WITH THE NATIONAL ROADS AUTHORITY SPECIFICATION FOR ROAD WORKS IS TO BE USED AS BACKFILL MATERIAL WHERE THE SEWER MAIN IN IS LOCATED ROADS, FOOTPATHS OR WHEN THE NEAREST PART OF THE TRENCH IS WITHIN 1m OF THE PAVED EDGE OF THE ROADWAY. CLAUSE 808 IS TO BE COMPACTED AS PER CLAUSE 802 OF THE NATIONAL ROADS AUTHORITY SPECIFICATION FOR ROAD WORKS,
- 4. SELECTED EXCAVATED MATERIAL MAY BE USED IN GREEN-FIELD AREAS ABOVE GRANULAR PIPE SURROUND MATERIAL SUBJECT TO APPROVAL BY IRISH WATER.
- 5. PIPE BEDDING SHALL COMPLY WITH WIS 4-08-02 AND IGN 4-08-01. GRANULAR MATERIAL SHALL BE 14mm TO TO 5mm GRADED AGGREGATE OR 10mm SINGLE SIZED AGGREGATE TO IS EN 13242.
- 6. IN SOFT GROUND CONDITIONS (CBR <5) THE MATERIAL SHOULD BE EXCAVATED AND DISPOSED OF IN ACCORDANCE WITH THE WASTE MANAGEMENT ACT AND CLAUSE 808 IN MATERIAL IN ACCORDANCE WITH THE NATIONAL ROADS AUTHORITY SPECIFICATION FOR ROAD WORKS SHALL REPLACE THE EXCAVATED MATERIAL, WRAPPED IN GEO-TEXTILE WRAPPING, ALTERNATIVELY, SPECIAL PIPE SUPPORT ARRANGEMENTS, INCLUDING PILING ETC. MAY BE REQUIRED WHERE THE DEPTH OF SOFT MATERIAL IS EXCESSIVE. SUCH ARRANGEMENTS SHALL BE SUBJECT TO ASSESSMENT BY IRISH WATER BEFORE ADVANCING WITH THE WORK.
- 7. PIPES SHALL NOT BE SUPPORTED ON STONES, ROCKS OR ANY HARD OBJECTS AT ANY POINT ALONG THE TRENCH. ROCK SHALL BE EXCAVATED TO A DEPTH 150mm BELOW THE ACTUAL DEPTH OF THE TRENCH WITH THE VOID FILLED WITH CLAUSE 808 MATERIAL IN ACCORDANCE WITH THE NATIONAL ROADS AUTHORITY SPECIFICATION. FOR ROAD WORKS. THE GRANULAR MATERIAL SHALL BE LAID ABOVE THIS VOID **BACKFILL MATERIAL**
- 8. SHOULD MINIMUM COVER NOT BE ACHIEVABLE, CONCRETE GRADE C8/10 SHALL BE USED AS BACKFILL MATERIAL.
- 9. MARKER TAPE SHOULD BE 400mm WIDE BLUE POLYETHYLENE MATERIAL IN ACCORDANCE WITH EN12163, PLASTIC PIPES SHALL HAVE WARNING TAPE INCORPORATED A REINFORCED BAND BRACING WIRE.SERVICE PIPES SHALL HAVE 200mm WIDE MESH TAPE.MARKER TAPE TO BE LAID AT TOP OF PIPE BEDDING LAYER.
- 10. TRENCH WIDTHS FOR PIPE SIZES <80mm MAY BE <500mm. SUBJECT TO CONSIDERATION BEING GIVEN TO THE TRENCH DEPTH, HEALTH & SAFETY AND CONSTRUCTION ACCESS REQUIREMENTS.

## General Notes


- I. No part of this document may be re-produced or transmitted in any form or stored in any retrieval system without the written permission of the Consulting Engineer, David Kelly Partnership, as copyright holder except as agreed for use on the project for which the document was originally issued. 2. The contractor is responsible for checking all levels and dimensions of
- site and shall refer all discrepancies to the Engineer
- 3. Only drawings issued for CONSTRUCTION shall be used fo
- 4. Work to figured dimensions only. Do not scale print.
- Check size of drawing sheet against dimension marks at bottom lef hand corner of sheet.

PIPE DIAMETER 'A' (mm)	TRENCH WIDTH 'B' (mm)
<80	SEE NOTE 10
100	500
150	600
200	600
250	750
300	750
350	750
400	900
450	900

PIPE DIAMETER '	A' (mm) DEPTH OF BEDDING 'C
<200	150
>250	200

## NOTE:

ALL WORKS TO COMPLY WITH IRISH WATER CODE OF PRACTICE AND STANDARD DETAILS AGREED IN ADVANCE OF WORKS





Youghal, Co. Cork.

Nelson House, Emmet Place, 10 Ormonde Street, Kilkenny. t +353 (0)56 7801260

t +353 (0)24 92412

e. info@dkp.ie www.dkp.ie

TIPPERARY COUNTY COUNCIL RESIDENTIAL DEVELOPMENT AT GROVE STREET, ROSCREA, CO. TIPPERARY

ARCHITECT: C.J.FALCONER & ASSOCIATES

WATERMAIN -TRENCH BEDDING AND BACKFILI

Purpose of Issue : PART 8 PLANNING NTS Project No. Issue No. 21049 108 P1

SHEET SIZE · A3